

Facestock

Extrusion coated three layer laminate (C1S paper 50gsm / LDPE $12/6.5\mu$ Alu foil / 25g PE)

Heat Seal front 150-180 °C

Moisture vapor transmission Max Astm F 1249

rate 0.5 g/sqm/24h (38°C;

90%RH) Max ASTM D3985

0.5 cm³/m²/24

hr

Tensile strength MD Min 5.5 daN/15 ASTM D828

mm

Tensile strength CD Min 2.5 daN/15 ASTM D828

mm

Tear Strength MD MIN 350 mN ISO 1974
Tear Strength CD MIN 400 mN ISO 1974


Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

AN048

Fasson ®

PAPER WEB50



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000

Oxygen Permeability

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com



©2023 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.